

# DUROSTICK SUPER



Luxury emulsion paint



## PROPERTIES

Emulsion, ultra-white luxury paint, of low odor. With strong adhesion, applies easily and dries quickly. Distinguished for its high performance and coverage, its uniform coat, and the velvety smooth, matte finish that uniquely highlights any shade. Does not yellow over time, it is particularly resistant to frequent washing (does not saponify) and does not fade. It allows for the breathability of surfaces, being at the same time water vapour permeable.

## APPLICATIONS

DUROSTICK SUPER emulsion paint is ideal for the protection and decoration of new and existing, painted surfaces made of plaster and concrete, gypsum board, spackled surfaces, chip-board etc. both indoors and out. Due to its durability against daily washing, it is ideal for public areas, such as hospitals, hotels, gyms, schools, kindergartens, restaurants, but also children's rooms etc.

## USE

### 1. Substrate preparation

Surfaces from concrete and marble based plaster have to be dry, at least 30 days from their construction, and free from loose materials.

**Surfaces soiled with soot and air pollution,** are cleaned with the biodegradable cleaner BIO-CLEAN (for nicotine and soot) or they are primed with METAL PRIMER of DUROSTICK.

**Already painted, sound surfaces** two coats with DUROSTICK SUPER are enough.

### 2. Application

Dilute DUROSTICK SUPER with water at a ratio of 5-10%, depending on the substrate, and stir well.

Both DARK and TRANSPARENT bases are diluted with water at a ratio of 2-5%. Apply with brush, roller or airless spray gun in 2 coats. Apply the second coat, after the first one is completely dry.

# DUROSTICK SUPER



Luxury emulsion paint

## CLEANING

Clean all tools with water and detergent solution, immediately after use.

## PERFORMANCE

Approximately 11-13m<sup>2</sup>/lt per coat, depending on the texture, the absorbency of the surface and the application method.

## STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

## NOTE

If needed, it is recommended to clean the freshly painted surface that DUROSTICK SUPER was used, with a soft sponge and mild detergent, 15 days after its application.

## SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

## LIMITATION OF USE

Do not apply if there is a chance of rain or frost within the next 12 hours.

## PACKAGING

Carton box with 12 pcs of 750ml each one  
3lt container (on a 120 pcs pallet)  
10lt container (on a 48 pcs pallet)

## TECHNICAL SPECIFICATIONS

<b>Color</b>	White, that does not yellow over time
<b>Shades</b>	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors. The PAL, DARK and TRANSPARENT bases are colored via the COLOR COLLECTION System in any desired color.
<b>Washability</b>	> 19,000 cycles (per DIN 53778)
<b>Gloss</b>	Matte
<b>Drying time</b>	1 hour (touch dry), depending on the ambient conditions
<b>Recoating time</b>	4-5 hours, depending on the ambient conditions
<b>Application temperature</b>	From +8°C to +35°C
<b>Flammable</b>	No
<b>V.O.C. (Volatile Organic Compounds):</b> <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/c: 'Coatings for exterior walls of mineral substrate' Type WB): 40 gr/lt (2010). The ready to use product contains maximum 39 gr/lt V.O.C.</i>	

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS  
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612  
THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367  
E-mail: [info@durostick.com](mailto:info@durostick.com)