

SUPER ECO



Ecological emulsion paint for interior & exterior use



PROPERTIES

Certified, ecological latex paint, that is odorless. Highly durable to frequent washing and adverse weather conditions. It ensures exceptional coverage, applies evenly and yields velvety smooth surfaces. It has excellent adhesion and does not splash during application. Approved by the Supreme Council of Ecologic Sign Conferment (YPEKA) and the EU Ecolabel for its composition. That composition does not contain any harmful substances, such as ammonia, formaldehyde and aromatic hydrocarbons.

APPLICATIONS

SUPER ECO is suitable for painting children rooms, kindergartens, schools hospitals and in general, places where strict hygiene standards are required. Ideal for **interior** use.

USE

1. Substrate preparation

Surfaces from concrete and marble based plaster have to be dry, at least 30 days from their construction, and free from loose materials.

For new marble based plaster surfaces, sand with sandpaper No60, apply STUCOFIX-P or POWDER COAT of DUROSTICK, depending on the imperfections of the surface and how smooth the finish we wish to have. Then, apply the micromolar stabilizer AQUAFIX or 100% ACRYLIC PRIMER of DUROSTICK.

Already painted, sound surfaces two coats of SUPER ECO of DUROSTICK are enough.

Surfaces soiled with soot, are cleaned with the biodegradable cleaner BIOCLEAN (for nicotine and soot).

For peeling surfaces, remove all loose materials and prime using 100% ACRYLIC PRIMER, or micromolar stabilizer AQUAFIX of DUROSTICK.

Fill the joints around door and window casings, by using the paintable ACRYLIC CAULK

SUPER ECO



Ecological emulsion paint for interior & exterior use

for interior use, the elastomeric sealant DUROFLEX-PU of DUROSTICK for exterior use, or the versatile sealant and adhesive for interior/ exterior use, DS POLYMER, available in 32 colors.

2.Application

Dilute DUROSTICK SUPER ECO with water at a ratio of 5-10%, depending on the substrate, and stir well. Apply with brush, roller or airless spray gun in 2 coats. Apply the second coat, after the first one is completely dry.

CLEANING

Clean all tools with water and detergent solution, immediately after use.

PERFORMANCE

Approximately 9.5-10.5m²/lt per coat, depending on the texture, the absorbency of the surface and the application method.

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date. The product will keep until its next use, if sealed properly.

NOTE

If one chooses a dark color, it is absolutely necessary first apply the micromolar stabilizer (primer) AQUAFIX of DUROSTICK.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs of 750ml each one
3lt container (on a 100 pcs pallet)
10lt container (on a 48 pcs pallet)

TECHNICAL SPECIFICATIONS	
Color	White, that does not yellow over time
Shades	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors. The PAL, DARK and TRANSPARENT paint bases are colored via the COLOR COLLECTION System in any desired color.
Washability	> 22,000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on the ambient conditions
Recoating time	3-4 hours, depending on the ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No
V.O.C. (Volatile Organic Compounds): <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/a: 'Matte coatings for interior walls and ceilings' Type WB): 30gr/lt (2010). The ready to use product contains maximum 10gr/lt V.O.C.</i>	

SUPER ECO



Ecological emulsion paint for interior & exterior use



DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.