

# DUROSTICK TEAK OIL



Natural oil with wax for the protection & maintenance of wood



## PROPERTIES

Natural oil that contains wax, natural and synthetic resins, and UV filters. Its periodic use preserves, revitalizes, and offers vitality and shine, highlighting the natural appearance of wood and upgrading its aesthetics. It protects wood from moisture, salt, and solar radiation. It is colorless, and allows for the breathability of wood since it does not form a surface skin.

## APPLICATIONS

TEAK OIL is suitable for the effective maintenance of balcony and garden furniture, boat decks, as well as all boat parts that are soaked with water that are made of wood. Apply it on hard woods and wood such as teak, mahogany, iroko, and any other bare wood, indoors and out.

## USE

### 1. Surface preparation

Remove all existing paints and varnishes with sandpaper #80. Continue by fine-sanding the surface with a larger number sandpaper and

thoroughly remove all the dust. If the wood surfaces are soiled from oils, salts etc. it is highly recommended to clean them first with WOOD CLEANER of DUROSTICK. Rinse thoroughly with plenty of water and let them dry. The cleaning process will remove the 'annoying' accumulated stains and restores to the wood surfaces their natural color.

### 2. Application

Shake well TEAK OIL before use and make sure all wood surfaces are completely dry. Apply 1-2 coats of the product undiluted. It is necessary to allow 5-8 hours between coats (or once the first coat is thoroughly dry), to achieve proper protection of the wood surfaces. Five to ten minutes after the application of each coat, use a dry, soft (cotton) cloth to remove any excess material.

## CLEANING

Clean all tools with THINNER 101 of DUROSTICK or white spirit immediately after use.

# DUROSTICK TEAK OIL



Natural oil with wax for the protection & maintenance of wood

## PERFORMANCE

Approximately 10-13m<sup>2</sup>/lt per coat, depending on the absorbency of wood.

## STORAGE

Store in shaded places away from any heat source, for at least 24 months from production date.

## SAFETY DIRECTIONS

The product is classified as harmful and flammable. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product label or the Material Safety Data Sheet.

## PACKAGING

- Carton box with 12 pcs of 750ml each one
- Carton box with 4 pcs of 2.5lt each one

## TECHNICAL SPECIFICATIONS

|                                |                                |
|--------------------------------|--------------------------------|
| <b>Form - Color</b>            | Oily liquid - Semi transparent |
| <b>Density</b>                 | 0.80±0.05kg/lt                 |
| <b>Application temperature</b> | From +5°C to +35°C             |
| <b>Odor</b>                    | Light odor, odorless when dry  |

**V.O.C. (Volatile Organic Compounds):** Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/f: 'Interior and exterior minimal build woodstains' Type SB): 700gr/lt (2010). The ready to use product contains maximum 560gr/lt V.O.C.

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367

E-mail: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.