

# DUROSTICK THINNER 101



Enamel paint thinner



## PROPERTIES

THINNER 101 is a special composition, clear dilution liquid for enamel paints. Its formula contains a mixture of aromatic and aliphatic hydrocarbons and special additives. Its composition prevents foaming that is usually observed when using common thinners or white spirit.

## APPLICATIONS

Ideal for diluting oil based paints, alkyd varnishes, and solvent based primers when applying with roller or brush. Due to its composition, it is used for the cleaning of painting tools (rollers, brushes etc.). Suitable for the thorough cleaning of metal surfaces before they are primed or painted. Use it to remove oils, grease and other pollutants from engines, spare parts and various equipment.

## USE

**As thinner:** THINNER 101 is added directly to the material to be diluted. Add 1-5% in varnishes,

5-10% in oil based paints and 50-100% in solvent based primers, depending on the application. Follow the instructions printed on the packaging of the product. Stir well until the mixture becomes homogeneous.

**As cleaner:** Use it as is, does not require rinsing. After its use, just allow for all the tools, metal surfaces and various objects to dry.

## CONSUMPTION

50-100ml/lit of enamel paint.

## SAFETY DIRECTIONS

The product is classified as harmful and flammable. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

## STORAGE

Store in places protected from high temperatures, direct sunlight and away from any heat

# DUROSTICK THINNER 101



Enamel paint thinner

source, for at least 12 months from production date.

## PACKAGING

Carton box with 20 pcs of 400ml each one  
Carton box with 20 pcs of 750ml each one  
Carton box with 6 pcs of 4lt each one  
15lt container

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	0.80±0.02kg/lt
Application temperature	From +5°C to +35°C
Contains special silicone additives to prevent foaming	

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:  
+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55  
98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,  
STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30  
2310 797 365, Fax: +30 2310 797 367

E-mail: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.