



DECLARATION OF PERFORMANCE

DoP [EN] No. 056 DURO-CPR-7-2013

1. Unique identification code of product-type:
DUROSTICK ULTRACOLL THERMO
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The coding shown on the packaging is the production date of the product.
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
General purpose rendering mortar for insulation GP: CSIV/W2
4. Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4.
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 998-1: 2010
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
9. Declared performance:

Essential characteristics	Declared performance	Harmonised Appropriate Documentation	standard /Technical
Reaction to fire:	Euroclass (A1/A1_{fl})		
Compressive strength	CSIV	EN 1015-11	
Adhesion	> 1N/mm² - FP:B	EN 1015-12	
Capillary water absorption	W2	EN 1015-18	
Water vapour permeability	μ 5/20	EN 1015-19	
Thermal Conductivity (λ10, dry)	0.55	EN 1745:2002 table A.12	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa



DUROSTICK S.A

ASPROPYRGOS ATHENS PC: 19300

GREECE

11

EN 998-1:2010

ULTRACOLL THERMO

DoP No. : 056

General purpose rendering mortar

Internal-External use

GP: CSIV/W2

Reaction to fire : Euroclass A1

Adhesion: > 1N/mm² - FP: B

Water absorption: W2

Water vapour diffusion coef.: μ 15/35

Thermal conductivity ($\lambda_{10,dry}$): 0.82 (Tab. Mean value; P=50%)

Durability: (against freeze/thaw): evaluation based on provisions valid in the intended place of use of the mortar