

DUROSTICK WOOD CLEANER



Cleaner for woodwork and garden furniture



PROPERTIES

Powerful cleaning liquid with active ingredients. The product presents excellent penetrating ability in hard or soft wood pores. Use it to remove difficult, accumulated stains such as oils, salts etc. Ready to use and easy to apply, it restores woods to their natural color without destroying them.

APPLICATIONS

DUROSTICK WOOD CLEANER is a highly effective cleaning liquid for exterior wood surfaces and constructs, terrace and garden furniture (tables, chairs, benches etc.), as well as pergolas, wood patios and pool decks, pleasure boat decks and other wood surfaces (existing doors and windows) which must be cleaned before their protection with TEAK OIL or DUROSTICK wood protection varnishes. The product can also be used at regular intervals for the maintenance of any uncoated, bare wood surface.

USE

- Shake well before use.
- Soak the surface, spray the cleaning liquid and allow for it to act for 5 to 10 minutes.
- Using a cleaning sponge or a stiff broom (suitable for floor and deck cleaning), scrub the surface evenly, following the wood grain.
- Rinse with water during and immediately after the cleaning process. For severely weathered and heavily soiled surfaces, repeat the process.
- Allow for the clean surface to dry for, at least 24 hours before applying TEAK OIL or any other protective varnish (*)

(*)DUROSTICK highly recommends after cleaning with WOOD CLEANER, and all surfaces have dried thoroughly, apply the clear impregnation preservative DUROXYL WOOD Protection / Conditioner to protect the woodwork (doors, windows, pergolas, overhangs, fences, balcony and terrace balusters etc.). For additional protection, especially from intense sunshine on outdoor surfaces, it is highly recommended to apply either

DUROSTICK WOOD CLEANER



Cleaner for woodwork and garden furniture

DUROLAC (available in satin or gloss finish of DUROSTICK).

NOTES

- Old varnishes or enamel paints are removed using DUROSTICK D-26 corrosive and remover for paints and varnishes.
- During the application and the rinse steps it is recommended to wear protective gloves

CONSUMPTION

1lt/6-10m², depending on the absorbency and type of the surface of the wood.

STORAGE

Store in shaded places, for at least 36 months from production date.

SAFETY DIRECTIONS

The product is classified as corrosive. It is recommended to keep away from the reach of children and apply in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

- Carton box with 12 pcs of 500ml each one
- Carton box with 12 pcs of 1.2lt each one

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	1.00±0.05kg/lt
pH	5.0±0,50
Application temperature	From +5°C to +35°C
Application method	Sponge, stiff broom
Dilution	Ready for use product. Does not dilute.
Flammable	No
Contains	Non-ionic surfactants less than 5% Anionic surfactants less than 5%
Friendly to human and the environment	
<i>Permit No. by General Chemical State Laboratory ELEFSIS 3093/2008</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:
 +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55
 98 350, Fax: +30 210 55 99 612
 THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30
 2310 797 365, Fax: +30 2310 797 367
 E-mail: info@durostick.com