

DECLARATION OF PERFORMANCE

No. 006

- 1. Unique identification code of the product-type: **SUPER ACRYLIC**
- 2. Intended use/es: Improved cementitious adhesive with reduced slip and extended open time
- 3. Manufacturer: DUROSTICK S.A., Paint, mortar & adhesive industry. Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr
- 4. Authorished Representative:
- 5. System/s of AVCP: System 3
- 6. Harmonised standard: EN12004:2007+A1:2012

Notified Body:

MIRTEC S.A. No. 0437 ITC DIVIZE CSI No. 1390

7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Bond strenght as:	
Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
Durability for:	
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Zoi Athanasiou - Head of Mortar Lab

Aspropyrgos 28.07.2023

CE MARKING

CE

DUROSTICK S.A.

ASPROPYRGOS-ATHENS PC: 19300

GREECE

07

DoP No. : 006

EN12004:2007+A1:2012

SUPER ACRYLIC

Improved cementitious adhesive with reduced slip and extended open time, for internal and external tiling

Reaction to fire Release of dangerous substances	Class A1 See SDS
Bond strenght as:	
Initial tensile adhesion strength	≥ 1.0 N/mm ²
Durability for:	
Tensile adhesion strength after heat ageing	≥ 1.0 N/mm ²
Tensile adhesion strength after water immersion	\geq 1.0 N/mm ²
Tensile adhesion strength after freeze-thaw cycles	\geq 1.0 N/mm ²