

DECLARATION OF PERFORMANCE

No. 061

1. Unique identification code of the product-type: **D-41**
2. Intended use/es: **General purpose rendering / plastering mortar (GP)**
For external and internal use
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr
4. Authorised Representative:
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN 998-1:2016**

7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Water absorption	W _c 2
Water vapour diffusion coeff.	μ 15/35
Adhesion	$\geq 0.65 \text{ N/mm}^2$ - FP: B
Thermal conductivity ($\lambda_{10,\text{dry}}$)	0.61 W/m · K (tab. value)
Durability (against freeze-thaw)	NPD
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Zoi Athanasiou - Head of Mortar Lab



Aspropyrgos **23.06.2023**

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

07
DoP No. : 061

EN 998-1:2016

D-41

General purpose rendering / plastering mortar (GP)
for external and internal use

Reaction to fire	Class A1
Water absorption	W _c 2
Water vapour diffusion coeff.	μ 15/35
Adhesion	≥ 0.65 N/mm ² - FP: B
Thermal conductivity (λ _{10,dry})	0.61 W/m·K (tab. value)
Durability (against freeze-thaw)	NPD
Dangerous substances	See SDS