## **DECLARATION OF PERFORMANCE**

No. 167

- 1. Unique identification code of the product-type: HYDROSTOP THERMO PLASTER FINE
- 2. Intended use/es: External renders and internal plasters based on organic binders
- 3. Manufacturer: DUROSTICK S.A., Paint, mortar & adhesive industry. Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr

-

- 4. Authorished Representative:
- 5. System/s of AVCP: System 4
- 6. Harmonised standard: EN 15824:2017
- 7. Declared performance/s:

Essential Characteristics	Performance
Water vapour permeability	V <sub>2</sub>
Water absorption	W <sub>3</sub>
Adhesion	0,4 Mpa
Durability	NPD
Thermal conductivity	$\lambda = 0, 7 \text{ W}/(\text{m} \cdot \text{K})$ Euroclass C
Reaction to fire	Euroclass C
Dangerous substances	According to paragraph 4.8

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Aristides Koutsibelis - Dr Chemist Manager Research & Quality Assurance

Aspropyrgos 27/07/2023

**CE MARKING** 

CE		
DUROSTICK S.A. ASPROPYRGOS-ATHENS PC: 19300 GREECE		
23		
DoP No. : 167		
EN 15824:2017 HYDROSTOP THERMO PLASTER FINE		
HIDROSTOP THERMO PLASTER FINE		
External renders and internal plasters based on organic binders		
Water vapour permeability	V <sub>2</sub>	
Water absorption	W <sub>3</sub>	
Adhesion	0,4 Mpa	
Durability	NPD	
Thermal conductivity	$\lambda = 0, 7 W/(m \cdot K)$	
Reaction to fire	Euroclass C	
Dangerous substances	According to paragraph 4.8	