

GEL COAT CLEANER



Acid cleaning agent for polyester boats



■ PROPERTIES

Active and low foaming professional acid cleaning agent, suitable for removing any surface rust from the gel coat around various metal components and parts. It quickly removes yellow, brown and black stains from the waterline and the hulls of boats, restoring them to their original color(s).

■ APPLICATIONS

GEL COAT CLEANER is applied on any kind of surface (polyester, metal, and even fiberglass) that requires effective cleaning.

Use it on boat hulls to easily remove hard sediment and microorganisms, salt stains, smudges, soot from

exhaust pipes and other persistent stains. Effectively removes rust from the rims of boat trailers.

■ USE

- During use and while rinsing, it is highly recommended to use protective goggles and plastic gloves.
- Shake well before use.
- Carefully empty the liquid into an open container and apply it with a paint brush.
- Allow for the cleaning agent to act for 10 minutes and rinse with a wet sponge or plenty of fresh water.
- On surfaces with tough dirt and stubborn stains, repeat the procedure.

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

GEL COAT CLEANER



Acid cleaning agent for polyester boats

■ CONSUMPTION

Depending on the application.

■ STORAGE

Store in places protected from sunlight and frost, for 18 months from production date.

■ SAFETY DIRECTIONS

The product is classified as corrosive.

It is recommended to keep it locked, away from the reach of children and apply it in well ventilated areas.

Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 12 pcs of 1lt each one
5lt containers (special order).

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid - Transparent
■ Density	1.30±0.05kg/lt
■ pH	0-1
■ Contains more than 10% phosphoric acid, less than 5% non-ionic surfactants & less than 5% anionic surfactants	

Permit No. By General Chemical State Laboratory
ELEFSIS: 3093/2008

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.