

((

DECLARATION OF PERFORMANCE

No. 115 DURO-CPR-7-2013: WATERPROOF MORTAR

1. Unique identification code of the product: **115**

2. Intended uses:

EN 1504-2: Surface protection products-Coating- Principle 2, Moisture Control (MC)

3. Manufacturer:

DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, <u>www.durostick.gr</u>

- **4.** Authorized representative:-
- **5.** System of AVCP (assessment and verification of constancy of performance): **System 4**
- 6a. Harmonized standard:

EN 1504-2:2004

Notified body: -

6b. European Assessment Document Technical Assessment Body

not applicable Technical Assessment Body

not applicable Notified Body

not applicable

7. Declared performance

Essential charecteristics	Performance	Test method	Harmonised Standard
Permeability to CO ₂	s _d >50m	EN 1062-6 (method A)	
Permeability to water vapour	s _d <5m, Class I (permeable)	EN ISO 7783-2	EN 1504-2:2004
Capillary absorption	$w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$	EN 1062-3	
Adhesion (pull-off test)	≥1,00N/mm²	EN 1542	
Reaction to fire after application	Euroclass F	EN 13501-1	
Dangerous substances	Comply with §5.3		

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Evdoxia Kafritsa

Function: Head of R&D, QC Mortars Dept. Place/Date: Aspropyrgos/ 2nd of January 2019

In accordance with Regulation (EU) 574/2014 amending the Regulation (EU) 305/2011



DUROSTICK S.A

ASPROPYRGOS ATHENS PC: 19300

GREECE

17

DoP No.: 115

EN 1504-2

WATERPROOF MORTAR

Surface protection product - Coating

Moisture Control

Permeability to CO₂:

 $s_d > 50m$

Water vapour permeability:

Class I (permeable)

Capillary absorption:

 $w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$

Adhesion (pull of test):

≥ 1.0 N/mm²

Reaction to fire:

Euroclass F

Dangerous substances comply with 5.3