

100% ACRYLIC PRIMER



■ PROPERTIES

Water soluble acrylic primer for emulsion and acrylic paints. It offers strong adhesion and presents high resistance to alkaline surfaces.

Stabilizes new surfaces to be painted and reduces their absorption capacity; thus increases the efficiency of the paints and doubles their life span. The primed surface ensures the color uniformity of the final coat.

Odorless, high performance, dries quickly and penetrates deeply.

■ APPLICATIONS

DUROSTICK's 100% ACRYLIC PRIMER it is recommend to be used prior to painting wall surfaces made of plaster and concrete, as well as surfaces coated with cementitious pastes. Remove any loose paints from surfaces already coated with emulsion and acrylic paints and prime them with a single coat of 100% ACRYLIC PRIMER, before repainting. -Suitable for any interior and exterior application.

■ USE

1. Surface preparation

All surfaces to be primed have to be clean, dry, and free from loose sections, dust, and formwork oils.

Absorbent surfaces have to be primed with one part 100% ACRYLIC PRIMER and two parts water. On low absorption surfaces, the mixing ratio has to be 1:3, to avoid the creation of a glossy film.

2. Application

The diluted product must be mixed well before application and periodically, to avoid separation of ingredients.

Apply it with a roller, brush or airless spray gun.

■ CLEANING

Clean all tools with water and detergent solution immediately after use.

■ COVERAGE

Approximately 10-15m²/lt, depending on the absorbency and dilution, on properly prepared surfaces.

■ STORAGE

Store in places protected from frost, for 18 months from production date.

100% ACRYLIC PRIMER



■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation.

However, it is recommended to keep away from the reach of -children.

If swallowed, seek immediate medical advice and show the container or label.

■ PACKAGING

Carton box with 12pcs of 750ml each one
3lt, 10lt containers

TECHNICAL SPECIFICATIONS	
■ Form - Color	Concentrated acrylic emulsion - White, becomes transparent when dry
■ Density	1.00±0.03kg/lt
■ Application temperature	From +5°C to +35°C
■ Drying time	1 hour (touch dry), at 25°C
■ Painting	After 4-6 hours, depending on the ambient conditions

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for the particular product (Class A/h: 'Binding primers' Type WB): 30gr/lt (2010). The ready to use product contains maximum 14gr/lt V.O.C.

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.