

# PRIMER-PU



## Primer for polyurethane sealants



### ■ PROPERTIES

A mixture of isocyanate prepolymers, suitable for increasing the adhesion of each type of polyurethane sealant to be applied on porous surfaces. Its application improves grip and ensures long lasting, unbreakable and complete bonding.

### ■ APPLICATIONS

PRIMER-PU of DUROSTICK is applied to surfaces made of concrete and plaster, bricks, clay roof tiles, cement boards, aircrete, marble, etc. It's necessary for priming the expansion joints on roofs, and the junctions between horizontal and vertical surfaces, as well as priming the perimeter joints of door and window frames.

### ■ USE

#### 1. Surface preparation

The substrate must be sound, dry and free from oils and dust.

#### 2. Application

Apply it undiluted, using a small, narrow brush. Apply PRIMER-PU on the porous surfaces and after an hour, the earliest, to three hours, the latest, apply the

polyurethane sealant, DUROFLEX-PU. After the application is completed, reseal the container in order to avoid the product coming in contact with any humidity.

### ■ CONSUMPTION

15-20ml/linear meter, depending on the width and depth of the joint.

### ■ STORAGE

Store in dry places, for 12 months after production date.

### ■ SAFETY DIRECTIONS

The product is classified as flammable and harmful. It is recommended to keep away from the reach of children and applied in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

### ■ PACKAGING

Carton box with 12 containers of 250ml

Carton box with 15 containers of 500ml

# PRIMER-PU



---

## Primer for polyurethane sealants

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid - Transparent yellow
■ Density	1.00±0.05 kg/lit
■ Drying time	2-3 hours, depending on weather conditions
■ Application temperature	From +10°C to +35°C

### VOC (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for this product (category A/h: 'Binding primers', Type SB): 750gr/lit (2010). The ready to use product contains maximum 444gr/lit V.O.C.

### DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,  
PAINTS & MORTARS

**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,

Tel: +30 211 60 03 500-599, +30 210 55 16 500,

+30 210 55 98 350, Fax: +30 210 55 99 612

**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367

Email: [info@durostick.com](mailto:info@durostick.com)

---

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.