

# CEILING PAINT



For ceilings



## ■ PROPERTIES

Waterborne paint with excellent whiteness and great coverage. Easy to apply, without lap marks, it dries thus it can be repainted quickly. It allows for the breathability of the ceiling, exceptionally useful in areas with concentrated water vapours. In this way, it prevents water vapour accumulation and condensation forming on the ceiling surfaces.

## ■ APPLICATIONS

DUROSTICK CEILING PAINT is exceptional for non thermally insulated ceilings, kitchen, baths, bedrooms, etc.

Affordable solutions for warehouse and stairwell applications. In addition, suitable for repainting already painted surfaces with ceiling paints or glue coating.

## ■ USE

### 1. Substrate preparation

Surfaces from marble-based plaster must be dry and smooth, free from loose sections, oils, mold, salts, dust, and at least 30 days after their construction.

**For new marble based plaster surfaces**, sand using No60 sandpaper or skim with GRANULAR or GRANULAR ULTRA to correct and cover any possible plaster surface defects.

**For already painted, sound surfaces**, without any cohesion problems, just apply 2-3 coats with DUROSTICK CEILING PAINT.

**For surfaces coated with whitewash or glue coating mixtures**, remove any peeling materials or bubbles with sandpaper, putty knife or electric sander.

**Surfaces infested with black or green mold or even active fungi**, necessarily have to be cleaned using DUROSTICK D-95 CLEANER, rinse thoroughly, dry and prime using SOLVENT BASED PRIMER or the micromolar stabilizer AQUAFIX of DUROSTICK.

### 2. Application

Dilute DUROSTICK CEILING PAINT with water at a ratio of 5-10%, depending on the substrate, and mix well. Apply with brush, roller or airless spray gun in 2-3 coats. Apply each additional coat, after the previous one is completely dry.

# CEILING PAINT



## For ceilings

### ■ CLEANING

Clean all tools with water and detergent solution, immediately after use.

### ■ COVERAGE

Approximately 9-12m<sup>2</sup>/lt per coat, depending on the texture, the absorbency of the surface and the application method.

### ■ STORAGE

Store in places protected from sunlight and frost, for 18 months from production date.

### ■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

### ■ LIMITATION OF USE

Not recommended to apply on surfaces that are painted with emulsion, acrylic, or enamel paints.

### ■ PACKAGING

3lt container (on a 120pc pallet)  
9lt container (on a 48pc pallet)

## TECHNICAL SPECIFICATIONS

■ Color	White that does not yellow over time
■ Colors	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors.
■ Gloss	Matte
■ Drying time	1 hour (touch dry), depending on the ambient conditions
■ Recoating time	3-4 hours, depending on the ambient conditions
■ Application temperature	From +8°C to +35°C

### V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for the particular product (Class A/a: 'Matte coatings for interior walls and ceilings' Type WB): 30gr/lt (2010). The ready to use product contains maximum 3gr/lt V.O.C.

**DUROSTICK S.A.,**  
MANUFACTURING OF ADHESIVES,  
PAINTS & MORTARS  
**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
+30 210 55 98 350, Fax: +30 210 55 99 612  
**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
STREET, DA 10, GR: 570 22,  
Tel: +30 2310 795 797, +30 2310 797 365,  
Fax: +30 2310 797 367  
Email: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.