

DS-490



Reinforcing fiberglass mesh with 6x5mm mesh opening for cementitious brushable waterproofing mortars & spackling pastes



■ PROPERTIES - APPLICATIONS

Fiberglass mesh with 6x5mm mesh opening and 90gr/m² weight for integrated -reinforcement of cementitious waterproofing coatings and resinous spackling pastes for cement boards. Distinguished for its resistance to alkaline environments. Offers significant reinforcement and protects from capillary cracks resulting from temperature variations. Reinforces and bridges cementitious waterproofing coatings on balconies, roofs, pools, reservoirs and water towers.

■ PACKAGING

Roll 1m x 50m on a pallet with 48 pcs

TECHNICAL SPECIFICATIONS	
■ Form	Alkali resistant fiberglass mesh
■ Color	White

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.