



## Decorative & protective solvent-based wood varnish



### ■ PROPERTIES

Clear alkyd resin varnish of polyurethane modified base for interior and exterior wood surfaces. Suitable for soft and hard woods alike. It applies easily, displays great flexibility and spreads perfectly. It is highly resistant to moisture and snow. The UV filters contained in its formula, protect wood from ultraviolet rays of the sun. It highlights and protects the natural beauty of all types of wood, showcasing their grain.

### ■ APPLICATIONS

DUROLAC applies on every kind of woodwork that requires protection from impacts and stains, moisture and intense sunlight exposure. Apply it on doors, windows, frames, casings, fences, per-golas, wood sheds, overhangs, roofing beams, balcony, terrace railings, wood overhangs, furniture etc. Use it for interior and exterior spaces.

### ■ USE

#### 1. Surface preparation

Proper preparation ensures the best result in both new and existing wood. A necessary condition is the moisture of the woods and the humidity in the atmosphere to be at the lowest possible levels.

**New wood surfaces:** Before applying DUROLAC, the surfaces should be sanded with the appropriate sandpaper and the dusts should be well removed, while if there is resin, remove it with THINNER 101 by DUROSTICK. If necessary, fill any holes using DUROWOOD wood putty of DUROSTICK.

To preserve the natural color of the wood and protect against fungi, woodworm, blue stain and rot, apply a coat of DUROXYL Wood Protection / Conditioner, the solvent-based impregnating clear wood preservative of DUROSTICK. Also use the product as primer when changing wood color before the use of DUROXYL, the impregnating color wood stain, available in 11 colors.

Complete the application by applying 1-2 coats of DUROLAC (satin or gloss finish).

**Existing wood surfaces (\*):** If performing simple maintenance, lightly sand the wood and remove the dust completely. Existing varnishes and enamels in poor condition (deteriorated and/or peeling), have to be completely removed with coarse and fine sandpaper or use the corrosive remover D-26 of DUROSTICK. Complete the project following the same procedure as described at the 'New wood surfaces' paragraph.



## Decorative & protective solvent-based wood varnish

(\* ) If the wood is stained by difficult accumulated stains, such as oils, salts etc. it is recommended to clean it, using DUROSTICK WOOD CLEANER before the application. Rinse thoroughly with plenty of water and let it dry.

### 2. Application

Dilute DUROLAC with THINNER 101 of DUROSTICK or white spirit at a ratio of up to 5%.  
Apply with roller, brush or airless spray gun in 1-2 coats, depending on the application.

### ■ CLEANING

Clean all tools with THINNER 101 of DUROSTICK, immediately after use.

### ■ COVERAGE

Approximately 10-12m<sup>2</sup>/lt per coat, depending on the texture, the absorbency of the surface and the application method.

### ■ STORAGE

Store in shaded places away from any heat source, for 24 months from production date.

### ■ SAFETY DIRECTIONS

The product is classified as harmful and flammable. However, it is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

### ■ PACKAGING

Carton box with 12pcs of 750ml each one  
Carton box with 4pcs of 2.5lt each one

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid varnish - Transparent
■ Density	0.90±0.05kg/lt
■ Solids by weight	49±1% w/w
■ Solids by volume	40±1% w/v
■ Gloss	Satin, Gloss
■ Application temperature	From +5°C to +35°C
■ Drying time	3-5 hours (touch dry), depending on the ambient conditions (humidity, temperature)
■ Recoating time	After 8-10 hours, depending on the ambient conditions

### V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for the particular product (Class A/e: 'Interior/exterior trim varnishes and woodstains including opaque woodstains' Type SB): 400gr/lt (2010).  
The ready to use product contains maximum 399gr/lt V.O.C.

### DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,  
PAINTS & MORTARS

**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
+30 210 55 98 350, Fax: +30 210 55 99 612

**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
STREET, DA 10, GR: 570 22,  
Tel: +30 2310 795 797, +30 2310 797 365,  
Fax: +30 2310 797 367

Email: [info@durostick.com](mailto:info@durostick.com)