

DUROLUX RENOVATION TILE PAINT



Renovation paint for wall tiles & kitchen cabinets



■ PROPERTIES

High quality and durable, one-component acrylicpolyurethane paint. An advanced new technology, specially formulated paint and primer (2 in 1), for direct application over tiles. Distinguished for its strong adhesion, great coverage, and water vapor permeability. It is resistant to bathroom and kitchen conditions, condensation, and frequent washing (does not peel or emulsify). Due to the special fungicidal components contained within its formula, it can protect the film of paint its application creates as it does not promote mold creation or fungi growth. Easy to apply, with an excellent finish, it is the most affordable option to change color(s) and renovate, without making a mess (demolition, removal, and installation of new tiles or installation over existing tiles).

■ APPLICATIONS

DUROLUX RENOVATION TILE PAINT is ideal for the renovation of spaces with constant use and wear, such as bathrooms and kitchens.

Apply it to wall tiles, mosaics, and ceramics, but also to bathroom furniture and kitchen cabinets. Suitable for application on already painted and newly primed surfaces made of plaster, concrete, drywall, spackled walls, and ceilings. Ideal for residences, commercial spaces, rooms to let, student apartments, etc., for refreshing and renovating all surfaces, in bathrooms and kitchens.

■ LIMITATION OF USE

Not recommended for horizontal surfaces and surfaces where water pools.

■ USE

1. Surface preparation

The surfaces to be painted need to be sound, free of loose sections, peeling paints, oils, fat, salts, dust, etc. Clean all surfaces that turned black, as well as moldy surfaces, with DUROSTICK D-95 CLEANER, and then rinse thoroughly and allow the surfaces to dry. All application surfaces must be smooth, clean and completely dry.

DUROLUX RENOVATION TILE PAINT



Renovation paint for wall tiles & kitchen cabinets

2. Application

Mix DUROLUX RENOVATION TILE PAINT lightly before use. Apply as is, with a foam roller or brush in 2 coats. The second coat follows after the first has completely dried.

■ NOTES

- The relative humidity of the application area must be lower than 60%.
- Use the coated surfaces 5 days after the completion of the painting.
- If needed, it is recommended to clean the freshly painted surfaces that DUROLUX RENOVATION TILE PAINT was used, with a soft sponge and mild detergent, 20 days after its application.
- The product achieves maximum mechanical strength after 20-30 days.
- Color it through the DUROCOLOR system as follows: Choose one of the 120 color chart colors. Follow the recipe by multiplying the ml of each pigment by a factor of 1,2.

■ CLEANING

Clean all tools with water and, if necessary, soap or detergent, immediately after use.

■ COVERAGE

750ml are enough for 5m² and for 2 coats.

■ STORAGE

Store in places protected from sunlight and frost, for 18 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

■ PACKAGING

Carton box with 12pcs of 750ml each one 2.5lt container

TECHNICAL SPECIFICATIONS	
■ Color	White that does not yellow over time
■ Colors	The white is colored with 20 basic DUROCOLOR pigments (in 20ml syringe packaging) that create 120 permanent colors
■ Density	1.35±0.05kg/lit
■ Gloss	matte
■ Washability	> 20.000 cycles (per DIN 53778)
■ Dilution	The product is ready for use. Do not dilute.
■ Drying time	One hour (touch dry), depending on the temperature of the environment
■ Recoating time	At least 6-8 hour from the previous application. The estimated times are prolonged under cold and humid conditions
■ Application	Apply directly over the surface without primer
■ Application temperature	+8°C +35°C

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for the particular product (Class A/a: 'Matte coatings for interior walls and ceilings', Type WB): 30gr/lit (2010). The ready to use product contains maximum 29gr/lit V.O.C.

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367

Email: info@durostick.com