

DUROMAX



Improving construction resin for mortars - 100% acrylic



■ PROPERTIES

Advanced new technology acrylic polymer emulsion of high concentration, and nanomolar technology. It is ideal for improving cement and lime-based mortars and enhancing their properties:

- Increases adhesion to the substrate.
- Improves flexibility, watertightness and workability.
- Reduces cure-related shrinkage and prevents hair line cracks.
- Increases mass and surface strength.
- Facilitates the construction of thin coats, enhances abrasion resistance and prevents surface dusting.
- Resistant to cement and lime alkalinity.
- Does not re-emulsify after complete cure of the mortars.
- Increases the resistance of mortars to acids, salts, oils, petroleum products.
- Increases the resistance of plasters against moisture and frost that lead to their gradual deterioration.
- Reduces the water requirement in mortars.

■ APPLICATIONS

AS MASS ADMIXTURE

In concrete repairs: Mortar preparation with river, beach or quarry sand or specialized ready mixed (fine or coarse grain) mortars. The mixing ratio in each case is 1lt DUROMAX per 25kg of cement.

In building mortars: Creates a flexible bond between the mortar grains, thus preventing crack formation from minor earthquakes and man-made vibrations due to excavating equipment operating in adjacent areas (0.5-1.5lt DUROMAX per 25kg of cement).

In new or existing renders in need of repairs: It increases durability and watertightness properties of both, traditional and ready mixed plasters (0.5-1.5lt DUROMAX per 25kg of cement/ready mixed plaster).

As necessary additive to scratch coat plasters:

Ensures adhesion to insulation products, e.g. expanded or extruded polystyrene, etc. (1.0lt DUROMAX per 25kg of cement).

As necessary additive to base coat plasters:

Increases adhesion and mechanical strength (0.75lt DUROMAX per 25kg of cement).

DUROMAX



Improving construction resin for mortars - 100% acrylic

Durable cement screeds: Add 0.75-1.5lt DUROMAX per 25kg of cement to increase their mechanical strength as well as their abrasion resistance.

Durable floors: Enables the creation of thin cement screeds, eliminating the risk of their detachment (1.5lt DUROMAX per 25kg of cement).

In cementitious adhesives: Increases adhesion, durability, flexibility and watertightness (0.5lt DUROMAX per 25kg of cement).

In grouts and tile/marble adhesives: Enhance their watertightness and increases the adhesion and flexibility (0.75lt DUROMAX per 25kg tile/marble adhesive).

In brushable cementitious waterproofing mortars: Increases flexibility and mechanical strength (0.5lt DUROMAX per 25kg of cement).

■ APPLICATIONS

AS SPRAYABLE OR BRUSHABLE PRIMER

For surface stabilization of floors: On fresh concrete surfaces apply by spraying or brushing, at a dilution rate of 1:3 with water, to protect them from dehydration and to create abrasion resistant floors that do not dust.

For surface stabilization of unsound surfaces made of plaster, concrete or lightweight screeds (filling material): Dilute Duromax at a ratio of 1:4 with water, and spray or brush the surfaces.

■ USE

1. Surface preparation

For better results it is highly recommended that the application surfaces are lightly soaked, clean, free from loose sections, dust, formwork oils and paint etc.

2. Application

Shake well before use. Add the required amount into the mixing water of the mortar, always depending on the application.

■ CLEANING

Clean all tools with water, immediately after use.

■ CONSUMPTION

Depending on the application. From 1:1 to 1:8 parts of water.

■ STORAGE

Store in places protected from sun and frost, for 15 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

■ NOTES

- The thinner the coatings, the more than twice the amount of DUROMAX.
- When increased flexibility of cement or lime-based mortars is required, the dilution ratio is determined at 1:3, DUROMAX: water
- The minimum amount of DUROMAX is 750ml per 50kg of cement
- Do not allow for the product to be exposed to temperatures below + 5°C.
- If frozen, transfer to a warmer environment.

■ PACKAGING

Carton box with 15 pcs of 750ml each one
 Carton box with 6 pcs of 3.5lt each one
 18lt container
 1.000lt tank (special order)

DUROMAX



Improving construction resin for mortars - 100% acrylic

TECHNICAL SPECIFICATIONS	
■ Form - Color	Acrylic polymer emulsion - White, becomes transparent when dry
■ Bulk density	1.00±0.05kg/lt
■ Application temperature	From +5°C to +35°C
■ pH	10±1
■ Does not contain organic solvents	
■ The adhesion strength doubles after 28 days, per EN 1015-12.	

The experimental measurements were performed per EN 1015-12 within DUROSTICK chemical lab and were confirmed by the EBETAM audit (949/2010).

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.