

DUROXYL Wood Protection/Conditioner



Parasiticide - eliminates woodworms



■ PROPERTIES

Effective, low odor insecticide for immediate action. It protects any wood surface/object from wood-boring insects or larvae and provides immediate, long-lasting protection. It exterminates woodworms and stops the destruction of all wood objects.

■ APPLICATIONS

DUROXYL Wood Protection/Conditioner, effectively treats, all infected by woodworm, wood structures such as window frames and doors, floors, furniture, pergolas etc., for both exterior and interior surfaces.

■ USE

Mix well before and during use. Unscrew the safety cap. Place the tip of the bottle into the hole of the wood surface that was created by the woodworm. Press the vial for approximately 5 seconds so the insecticide can reach to the invisible nesting area of

the insect or larvae in order to exterminate it. After 24 hours, seal the hole(s) with DUROWOOD, the acrylic, waterborne wood putty of DUROSTICK. In case woodworm appearance in timber store rooms, it is highly recommended to apply DUROXYL Wood Protection/Conditioner, (available in 2.5lt and 15lt containers), by brushing, spraying or dipping every piece of wood that is infected.

Avoid using the product in hot or frosty conditions. Protect your hands with gloves and avoid any contact of the product with your face.

■ CONSUMPTION

Each 100ml vial can cure 1-2m² of wood surface, depending on the type and the absorbency of the treated wood.

DUROXYL Wood Protection/Conditioner



Parasiticide - eliminates woodworms

■ STORAGE

Store in shaded places, away from any heat source, for 24 months from production date.

■ SAFETY DIRECTIONS

The product is classified as harmful and flammable. However, it is recommended to keep away from the reach of children, and apply it in well ventilated areas. Before use, consult the precautionary information on the product label or in the Safety Data Sheet.

ATTENTION

It contains powerful insecticide, particularly harmful for any use other than the intended protection of wood.

KEEP AWAY FROM THE REACH OF CHILDREN.

■ PACKAGING

Paper box with 20 vials of 100ml each one

TECHNICAL SPECIFICATIONS	
■ Form - Color	Low viscosity liquid - Transparent
■ Density	0.80±0.05kg/lit
■ Solids by weight	6-10% w/w
■ Application temperature	From +5°C to +35°C
■ Drying time	1-2 hours, depending on the application temperature
■ Dilution	A ready to use product. Do not dilute.
■ Odor	Light, it becomes odorless when dry

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/EC) for the particular product (Class A/f: 'Interior and exterior minimal build woodstains' Type SB): 700gr/lit (2010). The ready to use product contains maximum 675gr/lit V.O.C.

Approval registration number: TP8-0125

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,

Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367

Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.