

# No40 PVA PRIMER



## Primer for interior use



### ■ PROPERTIES

Vinyl-based, water-soluble and flexible primer for interior use. It stabilizes porous surfaces to be painted and properly prepare them by increasing the grip between the substrate and the emulsion or acrylic paints. It reduces plaster absorbency, providing economy in the consumption of paint. Odorless, recommended for use even in poorly ventilated areas.

### ■ APPLICATIONS

PVA PRIMER is used on interior building surfaces coated with plaster/render, on skim coated surfaces as well as surfaces lined with chipboard and gypsum board. Alternatively, AQUAFIX and SOLVENT

BASED PRIMER of DUROSTICK is also recommended for gypsum board surfaces.

### ■ USE

#### 1. Surface preparation

Surfaces to be primed have to be clean, dry, free from loose sections and dust.

#### 2. Application

Mix well before use. Apply it with a brush or a roller, at ambient temperatures, from +5°C to +35°C. Dilute with clean, cool water at a ratio of 1 part PVA PRIMER to two parts water. Paint over it after 8 hours, depending on the ambient conditions (temperature - humidity)

### ■ CLEANING

Clean all tools with water and detergent solution immediately after use.

### ■ COVERAGE

Approximately 12-15m<sup>2</sup>/lt, depending on the absorbency of the surface and the dilution rate, on properly prepared surfaces.

### ■ STORAGE

Store in places protected from frost, for 18 months from production date.

### ■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation.

# No40 PVA PRIMER



## Primer for interior use

However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

### ■ PACKAGING

Carton box with 12pcs of 750ml each one  
3lt, 25lt containers

TECHNICAL SPECIFICATIONS	
■ Form - Color	Concentrated emulsion- White, becomes transparent when dry
■ Density	1.00±0.05kg/lt
■ Application temperature	From +5°C to +35°C
■ Drying time	3 hours at +20°C

### V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for the particular product (Class A/h: 'Binding primers' Type WB): 30gr/lt (2010). The ready to use product contains maximum 29gr/lt V.O.C.

**DUROSTICK S.A.,**  
MANUFACTURING OF ADHESIVES,  
PAINTS & MORTARS  
**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
+30 210 55 98 350, Fax: +30 210 55 99 612  
**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
STREET, DA 10, GR: 570 22,  
Tel: +30 2310 795 797, +30 2310 797 365,  
Fax: +30 2310 797 367  
Email: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.