

POWER THERMO



Low expansion PU adhesive foam for insulation boards



■ PROPERTIES

One-component, solvent-free, polyurethane bonding foam with exceptional adhesive strength, designated for professional use. It cures by reacting with humidity in the atmosphere, it presents excellent adhesion, high thermal and acoustic insulation and absorbs vibrations. It does not add extra weight to the construction, it provides great ease of use, transport and storage. At the same time, the speed of application saves time and money.

■ APPLICATIONS

POWER THERMO is suitable for bonding EPS and XPS insulation boards to building facade surfaces. It has exceptional adhesion to brick, aircrete, concrete, plaster, cement board, wood and metal surfaces. Ideal for both new construction as well as facade renovations. It participates in external thermal

insulation system for buildings as a bonding product for polystyrene boards.

■ USE

1. Surface preparation

The substrate must be sound, clean, free from dust, grease, oils, salts, mold etc. If fungi and/or algae are present on the application surface(s), remove them using the special purpose mold cleaner in spray form, DUROSTICK D-95 CLEANER. If any oils are present on the application surface(s), remove them using the biodegradable cleaner, BIOCLEAR INDUSTRIAL of DUROSTICK. In both cases, surfaces must be rinsed thoroughly with water and allowed to dry completely.

2. Application

- Shake well before use.
- Apply using a professional grade, special purpose gun for polyurethane foam.

POWER THERMO



Low expansion PU adhesive foam for insulation boards

- Place and screw the foam can (container) onto the gun.
- Adjust the flow of the product by rotating the flow control screw at the rear of the gun.
- Lightly soak the surface before applying the foam. Moisture is necessary because it improves adhesion and speeds up the cure time of the product.
- Apply the product around the edges of the insulation board, approximately 3-5cm away from the edges. Continue by applying successive strips between the outer edges, spaced 25-30cm from each other. The recommended strip thickness is approximately 10-12mm wide. Instead of applying straight strips between the outer edges of the insulation boards, apply the product in the shape of a 'W' or an 'M'.
- Install the insulation board to the building structure/facade within 5 minutes. The starting line/course of the insulation boards must be supported at their lower part with metal starting profiles to prevent the boards from slipping. Minor adjustments of the board(s) level and plumb are possible, but only when they are done within 10-15 minutes from the initial installation.
- Allow the product to cure for 30-40 minutes and install the mechanical fasteners/plugs.

■ NOTES

- For small pauses during application, the foam container can stay on the gun, so long as the flow control screw is tightened. If during the application and for any reason, it is necessary to stop using the product for a prolonged period of time, then the gun needs to be cleaned thoroughly using a special purpose spray.
- Replacing the POWER thermo can/container must be done quickly so as not to allow the foam to harden in it.

■ LIMITATION OF USE

- Not recommended for bonding insulation boards to surfaces made of polyethylene (PE), polypropylene (PP) and silicone.
- Not recommended for bonding insulation boards in areas with permanent underwater use or in groundwater level areas in general.

■ CLEANING

The cured (dried) foam can only be removed by mechanical means, such as a putty knife or razor blade. While the foam is still fresh on the application area and/or in the gun itself, clean it using a special purpose spray.

■ CONSUMPTION

An 830ml POWER THERMO container is sufficient for bonding insulation boards over an area of 10-13m². The product is also suitable for filling the gaps between the insulation boards, where necessary, to avoid the creation of thermal bridges.

■ STORAGE

Store at temperatures between + 5°C to + 25°C, in an upright position, for 12 months from production date.

■ SAFETY DIRECTIONS

The product is classified as highly flammable and harmful. It is recommended to keep locked away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 12 cans of 830ml each one

POWER THERMO



Low expansion PU adhesive foam for insulation boards

TECHNICAL SPECIFICATIONS	
■ Base	Polyurethane. ABSENCE OF SUBSTANCES (H)-CFC, PCB-H, formaldehyde
■ Density after curing	32-40kg/m3
■ Application temperature	From +5°C to +35°C
■ Temperature resistance after curing	From -40°C to +90°C
■ Touch dry/skin formation	7-8min (20°C, R.H. >30%)
■ Time for foam curing	1h / R.H. 93%, 18h R.H. 15% max 24h
■ Tensile strength at break (DIN 53455)	0.13MPa
■ Class B3 fire rating, per DIN 4102	
■ The product does not constitute food for insects and rodents	
■ Does not promote fungi or mold creation	

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.