

TEAK OIL



Natural oil with wax for the protection & maintenance of wood



■ PROPERTIES

Natural oil that contains wax, natural and synthetic resins, and UV filters. Its periodic use preserves, revitalizes, and offers vitality and shine, highlighting the natural appearance of wood and upgrading its aesthetics. It protects wood from moisture, salt, and solar radiation. It is colorless, and allows for the breathability of wood since it does not form a surface skin.

■ APPLICATIONS

TEAK OIL is suitable for the effective maintenance of balcony and garden furniture, balconies, boat decks. Apply it on hard woods and wood such as teak, mahogany, iroko, and any other bare wood, for interior and exterior spaces.

■ USE

1. Surface preparation

Remove all existing paints and varnishes with sandpaper No80. Continue by fine-sanding the surface with a larger number sandpaper and thoroughly remove all the dust.

If the wood is soiled with oils, salts etc. it is recommended to clean it, before the application, using DUROSTICK WOOD CLEANER. Rinse thoroughly with plenty of water and let it dry. The cleaning process will remove the annoying accumulated stains and restores to the wood surfaces their natural color.

2. Application

Mix TEAK OIL well before use and make sure all wood surfaces are completely dry. Apply 1-2 coats of the product undiluted. It is necessary to allow 5-8 hours between coats (or once the first coat is thoroughly dry), to achieve proper protection of the wood surfaces. Five to ten minutes after the application of each coat, use a dry, soft (cotton) cloth to remove any excess product.

■ CLEANING

Clean all tools with THINNER 101 of DUROSTICK or white spirit immediately after use.

TEAK OIL



Natural oil with wax for the protection & maintenance of wood

■ COVERAGE

Approximately 10-13m²/lt per coat, depending on the absorbency of wood.

■ STORAGE

Store in shaded places away from any heat source, for 24 months from production date.

■ SAFETY DIRECTIONS

The product is classified as harmful and flammable. However, it is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product label or the Safety Data Sheet.

■ PACKAGING

Carton box with 12pcs of 750ml each one
Carton box with 4pcs of 2.5lt each one

| TECHNICAL SPECIFICATIONS | |
|---------------------------|--------------------------------|
| ■ Form - Color | Oily liquid - Semi transparent |
| ■ Density | 0.80±0.05kg/lt |
| ■ Application temperature | From +5°C to +35°C |
| ■ Odor | Light odor, odorless when dry |

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for the particular product (Class A/f: 'Interior and exterior minimal build woodstains' Type SB): 700gr/lt (2010). The ready to use product contains maximum 699gr/lt V.O.C.

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com