

THINNER 101



Enamel paint thinner



■ PROPERTIES

A special composition, clear dilution liquid for enamel paints.

Its formula contains a mixture of aromatic and aliphatic hydrocarbons and special additives.

Its composition prevents foaming that is usually observed when using common thinners or white spirit.

■ APPLICATIONS

DUROSTICK's THINNER 101 is ideal for diluting oil-based paints, alkyd varnishes, and solvent-based primers when applying with roller or brush. Due to its composition, it is used for the cleaning of painting tools (rollers, brushes etc.). Suitable for the thorough cleaning (degreasing) of metal surfaces before they are primed or painted. Use it to remove oils, grease and other pollutants from engines, spare parts and various equipment.

■ USE

As thinner: THINNER 101 is added directly to the material to be diluted.

Add 1-5% in varnishes, 5-10% in oil-based paints and 50-100% in solvent-based primers, depending on the application. Follow the instructions printed on the packaging of the product. Mix well until the mixture becomes homogeneous.

As cleaner: Use it as is, does not require rinsing. After its use, just allow for all the tools, metal surfaces and various objects to dry.

■ CONSUMPTION

50-100ml/lit of enamel paint.

■ SAFETY DIRECTIONS

The product is classified as harmful and flammable. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

THINNER 101



Enamel paint thinner

■ STORAGE

Store in places protected from high temperatures, direct sunlight and away from any heat source, for 12 months from production date.

■ PACKAGING

Carton box with 20pcs of 400ml each one
Carton box with 20pcs of 400ml each one
Carton box with 6pcs of 4lt each one
15lt container

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid - Transparent
■ Density	0.80±0.02kg/lt
■ Application temperature	From +5°C to +35°C
■ Contains special silicone additive to prevent foaming	

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.