

WOOD CLEANER



Cleaner for woodwork and garden furniture



■ PROPERTIES

Powerful cleaning liquid with active ingredients. The product presents excellent penetrating ability in hard or soft wood pores. Use it to remove difficult, accumulated stains such as oils, salts etc. Ready to use and easy to apply, it restores woods to their natural color without destroying them.

■ APPLICATIONS

DUROSTICK WOOD CLEANER is a highly effective cleaning liquid for exterior wood surfaces and constructs, terrace and garden furniture (tables, chairs, benches etc.), as well as pergolas, wood patios and pool decks, pleasure boat decks and other wood surfaces (existing doors and windows) which must be cleaned before their protection with TEAK OIL or DUROSTICK wood protection varni-shes.

The product can also be used at regular intervals for the maintenance of any uncoated, bare wood surface.

■ USE

- Mix well before use.
- Soak the surface, spray the cleaning liquid and allow for it to act for 5 to 10 minutes.
- Using a cleaning sponge (for garden furniture) or a stiff broom (suitable for floor and deck cleaning), scrub the surface evenly, following the wood grain.
- Rinse with water 10 minutes after the cleaning process. For severely weathered and heavily soiled surfaces, repeat the process.
- Allow for the clean surface to dry for, at least 24 hours before applying TEAK OIL or any other protective varnish (*).

(*) DUROSTICK highly recommends after cleaning with WOOD CLEANER, and all surfaces have dried thoroughly, to apply the clear impregnation preservative DUROXYL WOOD Protection / Conditioner to protect the woodwork (doors, windows, pergolas, overhangs, fences, balcony and

WOOD CLEANER



Cleaner for woodwork and garden furniture

terrace balusters etc.). For additional protection, especially from intense sunshine on exterior surfaces, it is highly recommended to apply one to two coats DUROLAC (satin or gloss finish) of DUROSTICK.

■ NOTE

Existing varnishes and enamel paints, are removed with the corrosive remover D-26 of DUROSTICK.

■ CONSUMPTION

1lt/6-10m², depending on the surface and the absorbency of the wood.

■ STORAGE

Store in shaded places, for 36 months from production date.

■ SAFETY DIRECTIONS

The product is classified as corrosive. However, it is recommended to keep away from the reach of children and apply in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 12pcs of 500ml each one
Carton box with 12pcs of 1.2lt each one

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid - Transparent
■ Density	1.00±0.05kg/lt
■ pH	5.0±0.50
■ Application temperature	From +5°C to +35°C
■ Application method	Sponge, stiff broom
■ Dilution	A ready to use product. Do not dilute.
■ Contains	Non-ionic surfactants less than 5% Anionic surfactants less than 5%

Permit No. by General Chemical State Laboratory
ELEFSIS: 3093/2008

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.